

SEQ LINE

SUBMERSIBLE SEWAGE PUMP

Cast Iron impeller.

Cast iron hydraulic body.

Pumping sewage liquids.

Includes floating level.

Suitable for continuous heavy work.

Copper winding.

Cable length 26 feet.

Solid passage up to 1".

304 Stainless steel shaft.

Thermal protector IP 68 protection.

Class B insulation.

Stainless steel casing motor.



19591 NE 10th Ave - Miami, FL 33179 - BAY F & G

(786) 233-4203

www.schraiberpumpusa.com

sales@schraiberpumpusa.com

PERFORMANCE

SEQ LINE

SUBMERSIBLE SEWAGE PUMP

MODEL	Solid passage	Outlet	Hp	Kw	Amp	Volt	Phase	Frec (Hz)	Gpm	0.0	2.6	4.4	8.8	13.2	15.4	17.6	19.8
WQV4-6-0.25	1"	1"	0.3		5.2	115	1PH	60	H (ft)	25	25	24	21	20	19	18	17

MODEL	Solid passage	Outlet	Hp	Kw	Amp	Volt	Phase	Frec (Hz)	Gpm	0.0	11.0	22.0	33.0	44.0	55.0	66.0	88.0
WQD7-8-0.4G	1"	2"	0.6	0.4	7.5	115v	1PH	60	H (ft)	33	32	29	25	22	15		
WQ12D-10-0.75G	1"	2"	1	0.7	12	115v	1PH	60	H (ft)	49	46	45	42	33	25	16	
WQ12-10-0.75G	1"	2"	1	0.7	6	230v	1PH	60	H (ft)	49	46	45	42	33	25	16	

